



Award Winning True RMS Clamp Meter



We Made It Better!

- Magnetic hanger strap with flexible application
- Easy access battery latches. No screwdriver needed.
- Test lead storage for convenience
- Automatic AC/DC selection for Volts and Amps
- Added selection dial to navigate test functions
- Increased range of Volts and Capacitance
- Back probes included for mini-split applications



All The Pro Features You Love

- Same functionality as our popular DL429B
- 13 Key test functions
- More than 15 features
- Wireless to a Free App

Plus, Added Bonus Motor Tests!

- **3-Phase Motor Rotation Test** to confirm motor direction
- **Unbalanced Motor Test** to determine a motor's load efficiency
- **Low Pass Filter** to screen out unwanted higher frequencies from Variable Frequency Drives

Distinguished In The Marketplace

- 2-Year Limited Warranty
- Professional Safety Ratings

Available For A Great Price!

\$319⁹⁵ TNP





— BACKED BY —
UEI
QUALITY

2
YEAR
WARRANTY



DL500 Series Clamp Meter Comparison



Part #	DL569	DL579	DL589	DL599
UPC	053533509281	053533509274	053533509144	053533509137
TRMS		•	•	•
AC Volts	750V	750V	750V	1000V
DC Volts	1000V	1000V	1000V	1000V
AC current (amps)	400A	600A	600A	600A
DC current (amps)		600A	600A	600A
Resistance (Ohms)	40kΩ	60MΩ	60MΩ	60MΩ
Continuity/Diode	•	•	•	•
Capacitance (Farads)		6000μF	2000μF	9999μF
AC / DC microamps		2000μA	2000μA	2000μA
Frequency (Hertz)		99.99Hz - 99.99kHz	99.99Hz - 99.99kHz	99.99Hz - 99.99kHz
Duty cycle		•	•	•
Low Z (impedance)		•	•	•
LRA inrush		•	•	•
Temperature (K-type input)		-328° to 2462°F	-328° to 2462°F	-328° to 2462°F
NCV (LED & Audible)		•	•	•
Min/Max	•	•	•	•
Hold	•	•	Peak Hold	Data/Peak
Ranging	Auto	Auto/Man	Auto/Man	Auto/Man
Display count	4000 (3 3/4 dgt)	6000 (3 5/6 dgt)	6000 (3 5/6 dgt)	6000 (3 5/6 dgt)
Auto power off	•	•	•	•
Low battery warning	•	•	•	•
Test lead storage	•	•	•	•
Dual display	•	•	•	•
High voltage alert	•	•	•	•
Auto Calibration	•	•	•	•
Easy access battery latches	•	•	•	•
Backlight		•	•	•
Magnetic mount/strap	Optional	•	•	•
Worklight		•	•	•
Temperature differential		•	•	•
DC Zero		•	•	•
Auto AC/DC selection for V/A		•	•	•
Wireless to app		•	•	•
3-Phase motor rotation test		•	•	•
Motor unbalanced test		•	•	•
Low pass filter		•	•	•
Safety Rating	CATIV 300V CATIII 600V	CATIV 600V CATIII 1000V	CATIV 600V CATIII 1000V	CATIV 600V CATIII 1000V
Warranty	1-year limited	1-year limited	2-year limited	2-year limited

Safety Rated: CATIV 600V / CATIII 1000V
Certified by ETL to IEC 61010-1, 3rd edition



Includes

- Silicone Test Leads (ATL58)
- Back Probes (APB3)
- Alligator Clips (AAC3)
- Temperature Probes 2 (ATT29)
- Zippered Pouch
- Batteries 4 (AAA)
- Manual